

NFT 60103 LUCHAIRE

SCOPE

Petroleum products. Closed flash point of lubricants and fuels oils.

LUCHAIRE FLASH POINT TESTER AUTOMATIC VERSION

- **NLU 440** -

- **REF 40200** -

MAIN CHARACTERISTICS

- ✓ Test Temperature Range: Ambient to 400°C
- ✓ Automatic Flash point detection
- ✓ Data Storage: 200 results
- ✓ Automatic Flame Lightening and extinguishing
- ✓ Optional low gas cartridge to work in all types of environments
- ✓ Automatic Gas cut-off at the end of the test
- ✓ Emergency safety switch
- ✓ RS 232 C output
- ✓ Data acquisition Supervisor Software included possibility to collect the data for a LIMS

SCOPE OF DELIVERY

NLU 440 delivered ready for use with :

- REF 40213** Luchaire cup for temperatures above 100°C
- REF 40214** Luchaire cup for temperatures below 100°C
- REF 40386** Printer
- REF 40211** Pt 100 probe
- REF 40439** Insulated plate
1 m of gas tubing

OPTIONAL ACCESSORIES

- REF 40483** Gas cartridge case and 1 x 250ml gas cartridge

CONSUMABLES

- REF 40484** 100ml Gas cartridge for optional case
- REF 14110** Tube for butane propane gas 6 x 12 (10m)



ORDERING INFORMATION

REF 40200

NLU 440 For use on AC 230 V - 50 Hz - 0.3 A

REF 40200 / 115 V on request

(W) 320x (D) 580x (H) 360 mm (±17 kg)

CONTACT : sales@normalab.com

NORMALAB FRANCE SAS
ZA Caux Multipôles 1 - F-76 190 Valliquerville
Tel. : +33 232 700 100
Fax : +33 232 704 732

www.normalab.com

REF 40200 Leaflet 15

DISTRIBUTED BY

G-Labo Germany
Bgm.-Horneffstr.26
69509 Mörlenbach
Tel.: + 49 6209 797100
Fax: + 49 6209 797101
Mail: info@g-labo.de
Web: www.g-labo.de